








ErgoPack - Productrange

	Xpert Line The Benchmark in Ergonomic Pallet Strapping				Economy Line				
Model	700X	713X	726X	745X	700	700E	713E	726E	745E
									
Power	235W	235W	235W	235W	-	93W	93W	93W	93W
Drive	Electric motor with reinforced angle gear , electronically controlled				manually via a hand crank	Electric motor with spur gear , electronically controlled			
Battery Pack	3 x 12V AGM Battery	3 x 12V AGM Battery	3 x 12V AGM Battery	3 x 12V AGM Battery	-	2 x 12V AGM Battery	2 x 12V AGM Battery	2 x 12V AGM Battery	2 x 12V AGM Battery
Operating Voltage	36V	36V	36V	36V	-	24V	24V	24V	24V
Strapping cycles per battery charge (standard strapping*)	650	650	650	650	-	350	350	350	350
Charger	36V Charger, 4,5A	36V Charger, 4,5A	36V Charger, 4,5A	36V Charger, 4,5A	-	2 x 12V Dual Charger, 2A	2 x 12V Dual Charger, 2A	2 x 12V Dual Charger, 2A	2 x 12V Dual Charger, 2A
Chain speed	66m/min	66m/min	66m/min	66m/min	-	40m/min	40m/min	40m/min	40m/min
Pallets width setting	via Siemens Industrial Touchscreen in 10cm steps, works with work gloves				mechanically, by inserting a bolt in the appropriate position in 20cm steps				
Other settings	individual setting options via the Siemens Industrial Touchscreen, such as: <ul style="list-style-type: none"> • chain speed, • chain length, • standby timer, • strap lifter time for upper position, • Line Laser on / off, • Sealing Head on / off 				-	-	-	-	-
Indicators	<ul style="list-style-type: none"> • charging level indicated graphically and in %, • set pallet width, • permanent graphically indication of the ChainLance position, • strapping cycles, • sliding window open graphically and in writing, • safety instructions, • menu-driven step by step description for semi automated strap roll change 				-	3 LEDs indicating charging level and sliding window „open“			-
Software update	easy update via USB stick				-	only by manufacturer			

standard equipment

Model	700X	713X	726X	745X	700	700E	713E	726E	745E
									
AGR-Certification	✓	✓	✓	✓	✓	✓	✓	✓	✓
ChainLance				special, glass fiber reinforced, high strength soft-slide chain					
Tool-Lift	-	✓	✓	✓	-	-	✓	✓	✓
Sealing Head	-	✓	✓	✓	-	-	✓	✓	✓
Tension Force	-	150N – 1200N	400N – 2500N	400N – 4500N	-	-	150N – 1200N	400N – 2500N	400N – 4500N
Strap Types	PP/PET	PP/PET	PP/PET	PP/PET	PP/PET	PP/PET	PP/PET	PP/PET	PP/PET
Strap Width	9–25mm	9–13mm	12–16mm	15–19mm	9–25mm	9–25mm	9–13mm	12–16mm	15–19mm
Strap Thickness	0,5–1,3mm	0,35–0,85mm	0,5–1,0mm	0,8–1,3mm	0,5–1,3mm	0,5–1,3mm	0,35–0,85mm	0,5–1,0mm	0,8–1,3mm
Triplex-Tool-Lift	-	✓	✓	✓	-	-	✓	✓	✓
Sealing Head removable	-	✓	✓	✓	-	-	✓	✓	✓
Line Laser	✓	✓	✓	✓	-	✓	✓	✓	✓
Strap Brake Relief	✓	✓	✓	✓	✓	✓	✓	✓	✓
Reversing Sledge	47 / 47S	47 / 47S	47 / 47S	47 / 47S	47 / 47S / 85S	47 / 47S / 85S	47 / 47S / 85S	47 / 47S / 85S	47 / 47S / 85S
Header with Bumper	✓	✓	✓	✓	✓	✓	✓	✓	✓
Mobile Overheight Module	✓	✓	✓	✓	-	✓	✓	✓	✓
Stationary Sledge Tunnel	✓	✓	✓	✓	-	✓	✓	✓	✓
Mobile Sledge Tunnel Station	✓	✓	✓	✓	-	✓	✓	✓	✓
Ergonomic battery change trolley	✓	✓	✓	✓	-	✓	✓	✓	✓

* Standard strapping:

Battery pack: 100 charging- and discharging-cycles | Strap: 13 mm PET (complete strap roll) | Sealing Tool: 726, Tension Force 900 N without soft, Welding time 2 | Pallet: pallet width 0.8 m, pallet height 1.15 m | Strapping speed: fast | Room temperature: 20 °C

